

Fuyuutech HA 1189E



ITEM	TECHNICAL SPECIFICATIONS
EVALUATE	MIPS
FREQUENCY	380 MHz
FLASH	16 MB
SDRAM	32 MB
OPERATING SYSTEM	Linux
EVALUATE	MIPS
STANDARD INTERFACE RATE	RJ45
NETWORK PROTOCOL	10/100 Meters IP, TCP, UDP, DHCP, DNS, HTTP Server/Client, ARP, BOOTP, Auto IP, ICMP, Web socket, Telnet, FTP, TFTP, u PNP, NTP, SNMP, Modbus TCP
PORT NUMBER	1port (RS232 c RS485 c RS422)
STANDARD INTERFACE	RS232: DB9, RS485: 2 wire (A + B) RS422: 4 wire (T+ T-, R +, R-)
TRANSMISSION RATE	600 bps ~ 460800 bps
SIZE	95x65x25 (mm)
WORKING ENVIRONMENT	-40 ~ 70 ° C -45 ~ 105 ° C 5 ~ 95% RH (no condensation)
INPUT VOLTAGE	DC 5 ~ 36V

FUYUUTECH

IOT Scada

Smart Factory on Your Damnd



WWW.FUYUUTECH.COM



LINE : @MPENIOT