

WIFITEM & HUMIDITY TRANSMITTER

HT-485-DW

- Long-term stability
- **Wide measuring rand**
- Fast response time
- Support WIFI,PC,IOS and Android mobile App
- **4** 2.4inch color TFT screen



PRODUCT PARAMATER

Parameter

Item	Specification
Supply voltage	DC 9 to 36 V/USB 5V
Measuring range (T)	-20 to +60 Celsius(-4 to +140 Fahrenheit)
Measuring range (RH)	0 to 99.9% relative humidity
Typ. Temperature accuracy	±0.5 Celsius
Typ. Humidity accuracy	±3%RH at 25 Celsius
Long term drift(T)	<0.1 Celsius/year
Long term drift(RH)	<0.5%RH/year
Resolution(T)	0.1 Celsius
Resolution(RH)	0.1%RH
Display	2.4 inch TFT LCD screen
Power consumption	less than or equal to 50mA(24V)
Interface	WiFi
Protocols	Modbus TCP aggreement
Housing material	ABS
Net weight	175g



Website: www.mpen.co.th LINE OA: @mpeniot Tel. 02 101 9495, 065 693 6515, 065 539 8965




WIFI TEM & HUMIDITY TRANSMITTER

HT-485-DW

PRODUCT PARAMATER

Website: www.mpen.co.th

Dimension (mm)










LINE OA: @mpeniot Tel. 02 101 9495, 065 693 6515, 065 539 8965



WIFI TEM & HUMIDITY TRANSMITTER

HT-485-DW

PRODUCT PARAMATER WIFI Real Time Monitoring System





Website: www.mpen.co.th LINE OA: @mpeniot Tel. 02 101 9495, 065 693 6515, 065 539 8965



WIFI TEM & HUMIDITY TRANSMITTER

HT-485-DW

PRODUCT PARAMATER

Website: www.mpen.co.th

LINE OA: @mpeniot

Application





Tel. 02 101 9495, 065 693 6515, 065 539 8965